

Specifications

Fiber: 100% Polypropylene
 Weight: 290 gr. x m
 Width: 54" ± 1"

Performance

Breaking strength:	ASTMD 5034-09 Nwt	Warp 696.8	Fill 678.1
Elongation %:		54.2	54.8
Failure in sewn seams:	ASTMD 1683-11A Nwt	Warp 396.9	Fill 399.9

Color fastness:	AATCC-16 - 2014	4 - 5
Flame Resistance:	California Tech Bulletin	117-E IBE (2013)

Optional
 Flame Resistance: California Tech Bulletin 117-EDNI (2013)
 Stains: Stain Repellent

Cleaning Code
 Water based cleaning agents: (water based stains)
 Solvent cleaning agents: (oil based stains)

Colors may vary slightly between dye lots.

Not recommended for outdoor use or exposure to sunlight.



Especificaciones

Fibra: 100% Polipropileno
 Peso: 290 gr. x m.
 Ancho: 1.40 m. ± 2cm

Rendimiento

Resistencia a la tracción:	ASTMD 5034-09 Nwt	Urdimbre 696.8	Trama 678.1
Elongación %:		54.2	54.8
Deslizamiento de costura:	ASTMD 1683-11A Nwt	Urdimbre 396.9	Trama 399.9

Solidez a la luz:	AATCC-16 - 2014	4 - 5
Resistencia a la flama:	California Tech Bulletin	117-E IBE (2013)

Opcional

Resistencia a la flama: California Tech Bulletin 117-EDNI (2013)
 Manchas: Repelente a las manchas

Código de limpieza

Agentes base agua: (para manchas líquidas)
 Agentes base solvente: (para manchas aceitosas)

Pueden presentarse cambios de color de lote a lote.

No recomendada para exteriores o para exposición a la luz solar.



TEMPO XXI S.A. DE C.V.

Pasión por el servicio

Tel.: 58 12 53 81

58 12 01 38

52 45 21 83

Fax Ext.: 604

email: ventas@tempo21.com